

MATERIAL SAFETY DATA SHEET

MSDS 0094

 =====
 Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME	RectorSeal Tru-Blu	HMIS CODES	
		Health	1
		Flammability	2
		Reactivity	0
PRODUCT CODES	31300, 31431, 31551, 31631, 31780, 31785	PPI	B
CHEMICAL FAMILY:	Organic		
USE	Pipe Thread Sealant		
MANUFACTURER'S NAME	The RectorSeal Corporation	EMERGENCY TELEPHONE NO.	
	2601 Spenwick Drive	Chemtrec 24 Hours	
	Houston, Texas 77055 USA	(800) 424-9300	
VALIDATION DATE	February 19, 2007	TECHNICAL SERVICE TELEPHONE NO.	
REVISION DATE	February 19, 2007	(800) 231-3345	

 =====
 Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS

% by WT	CAS No.	INGREDIENT	UNITS
20-30	123-42-2	Diacetone Alcohol	
		ACGIH TLV	50 ppm
		OSHA PEL	50 ppm

 =====
 Section 3 -- HAZARDS IDENTIFICATION

SUMMARY OF ACUTE HAZARDS

Irritation to eyes, nose and throat; drowsiness, narcosis, tremors and other CNS effects at high concentration.

ROUTE OF EXPOSURE, SIGNS AND SYMPTOMS

INHALATION

Nasal and respiratory irritation, dizziness, narcosis, headache, nausea, CNS depression and unconsciousness.

EYE CONTACT

Watering, blurred vision, inflammation and irritation which can result in corneal injury.

SKIN CONTACT

Irritation, dermatitis.

INGESTION

Nausea, vomiting; CNS depression; irritation of gastrointestinal tract, liver and peritoneal wall; lung congestion.

SUMMARY OF CHRONIC HAZARDS

Skin irritation and dermatitis. Possible liver and kidney damage.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Individuals with pre-existing or chronic diseases of the eyes, skin, respiratory system, cardiovascular system, gastrointestinal system, liver or kidneys may have increased susceptibility to excessive exposures.

 =====
 Section 4 -- FIRST AID MEASURES

If INHALED: If overcome by exposure, remove victim to fresh air immediately. Give oxygen or artificial respiration as

FLASH POINT	LEL	UEL
150 F (65 C) SETA CC	N/D	N/D
EXTINGUISHING MEDIA		

Foam, dry chemical, carbon dioxide or water fog.

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus (SCBA) and other protective clothing. Hazardous decomposition products possible (see Section 10).

UNUSUAL FIRE AND EXPLOSION HAZARDS: Combustible - moderate flash point. Vapors heavier than air and may travel along the ground or to low spots at considerable distances to a source of ignition resulting in potential flashback. Burning liquid may float on water. Heat may build up pressure and rupture containers.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition. Use absorbent materials to prevent footing hazard and to contain. Ventilate area with natural or explosion-proof, forced air ventilation. Avoid flushing into sewers, drains, waterways, and soil. Wear protective clothing and respiratory protection during cleanup.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep container closed and upright when not in use. Do not store near heat, sparks, or open flames. OTHER PRECAUTIONS: Avoid prolonged or repeated contact with skin or clothing. Empty containers may contain residues; treat as if full and observe all products precautions. Do not reuse empty containers. KEEP OUT OF REACH OF CHILDREN.

RESPIRATORY PROTECTION (SPECIFY TYPE): In confined poorly ventilated areas,
use NIOSH/MSHA approved air purifying or supplied air purifying or
supplied air respirators.

VENTILATION - LOCAL EXHAUST: Acceptable

SPECIAL: Explosion-proof equipment.

MECHANICAL (GENERAL): Preferable

OTHER: N/A

PROTECTIVE GLOVES: Wear rubber gloves.

EYE PROTECTION: Chemical splash goggles (ANSI Z-87.1 or equivalent)

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Coveralls recommended.

WORK/HYGIENIC PRACTICES: Where use can result in skin contact, wash exposed
areas thoroughly before eating, drinking, smoking, or leaving work area.
Laundry contaminated clothing before reuse.

7/23/2007

BOILING POINT: 322 F (161 C) @ 760mm Hg
 SPECIFIC GRAVITY (H2O = 1): 1.38
 VAPOR PRESSURE (mm Hg): 0.3 @ 68 F (20 C)
 MELTING POINT: N/A
 VAPOR DENSITY (AIR = 1): 1.1
 EVAPORATION RATE (ETHYL ACETATE = 1): 0.14
 APPEARANCE/ODOR: Blue Paste/Mild Odor
 SOLUBILITY IN WATER: 23%

VOLATILE ORGANIC COMPOUNDS (VOC) Content
 (Theoretical Percentage By Weight): 23% or (230 g/L)

=====
 Section 10 -- STABILITY AND REACTIVITY
 =====

STABILITY: Stable
 CONDITIONS TO AVOID: Heat, sparks, open flames, and strong oxidizing.
 Temperatures above 500 F (260 C).
 INCOMPATIBILITY (MATERIALS TO AVOID): Gaseous oxygen, strong oxidizing
 materials, molten alkali metals.
 HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO2 and fragmented hydrocarbons.
 HAZARDOUS POLYMERIZATION: Will not occur.

=====
 Section 11 -- TOXICOLOGY INFORMATION
 =====

CHRONIC HEALTH HAZARDS

No ingredients in this product is an IARC, NTP or OSHA Lister carcinogen.

TOXICOLOGY DATA

Ingredient Name

Diacetone Alcohol

Oral-Rat LD50: 4000 mg/kg
 Inhalation-Human TCLo: 100 ppm

=====
 Section 12 -- Ecological Information
 =====

ECOLOGICAL DATA

Ingredient Name

Diacetone Alcohol

Food Chain Concentration Potential N/A
 WATERFOWL TOXICITY N/A
 BOD N/A
 AQUATIC TOXICITY N/A

=====
 Section 13 -- DISPOSAL CONSIDERATIONS
 =====

Waste Classification: Non-regulated solid waste
 Disposal Method: Approved landfill
 Waste from this product is not considered hazardous as defined under the
 Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Dispose of in
 accordance with Federal, State, and Local regulation regarding pollution.

=====
 Section 14 -- TRANSPORTATION INFORMATION
 =====

DOT: Non-Regulated
 OCEAN (IMDG): Non-Regulated
 AIR (IATA): Non-Regulated
 WHMIS (CANADA): Non-Regulated

Section 15 -- REGULATORY INFORMATION

REGULATORY DATA

Ingredient Name

Diacetone Alcohol

SARA 313	N/A
TSCA Inventory	Yes
CERCLA RQ	N/A
RCRA Code	N/A

Section 16 -- OTHER INFORMATION

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). The information herein is given in good faith, but no warranty, expressed or implied is made. Consult RectorSeal for further information: (713) 263-8001